



IP 20/40

DOWN LIGHT - SPOT

APPLICATION

Use high-performance COB LED, Ra>80. Aluminum heatsink and unique die casting heatsink design ensure better heat dissipation.

INSTALLATION

Suitable for 5~18 mm thick ceiling board

APPROVALS & STANDARDS

Saudi Standard SASO 2902	Energy Efficiency, functionality & labeling requirements for lighting products
IECEE Certificate (1)	As per IEC60598-2-3:2002+A1:2011, IEC60598-1:2014+A1:2017
Power Supply Approval Marks (2)	UL/CSA/CE/ENEC/CCB/CCC
Degree of Protection (IP)	IEC 60529:2013

1) certificates are under process 2) type of approvals and certificates depends on selected driver



LUMINAIRE	AES-CT070
WATTAGE	8W
COLOR TEMP	3000K/4000K/6000K
CRI	80
LUMINOUS FLUX	>850lm
BEAM	20° 40° 60°
IP RATINGS	IP 20/40
MATERIAL	Die casting aluminum heatsink
FINISH	White black

DOWNLIGHT

CUTOUT & DIMENSION

MODEL	WATTS
AES-CT070	8W

LxWxH(MM)	CUTOUT (MM)
Ø90xH72mm	Ø70-80mm



ORDERING INFORMATION

MODEL	WATTAGE	CRI	CCT	DRIVER	DIMMING
AESCT070	8W	80	30	Ph	ND
AESCT070	8W	80 90	30 3000K	Tr Tridonic	ND Non Dim
			40 4000K	Ph Philips	TD Triac Dim
			60 6000K	Lf Lifud	VD 0/1-10VDim
				LT Ltech	DA DALI Dim
				ER EagleRise	