



SURFACE MOUNT CORE FAMILY




APPLICATION

Simple and elegant square down light for surface installation, aluminum body for good heat dissipation. You can install it in: Residential lighting, villas, public areas, Hotel, Kitchen, Shopping Mall, Restaurant etc....

APPROVALS & STANDARDS

Saudi Standard SASO 2902 *	Energy Efficiency, functionality & labeling requirements for lighting products -Part2-
IECEE certificate *	As per IEC60598-2-3:2002+A1:2011 IEC60598-1:2014+A1:2017
Power supply approval marks	UL/CSA/CE/ENEC/CCB/CCC
Degree of protection provided by enclosures, ingress protection(IP)	IEC 60529:2013

*: Approvals and certificate are under process.




TECHNICAL INFORMATION

FAMILY	Core
Wattage	10W 20W 30W 40W
CRI	80 90
CCT	2700K 3000K 3500K 4000K 5000K 5700K 6500K
Beam	38° 45°
Lumen	1000lm 2000lm 3000lm 4000lm
Finish	White
Material	Die-casting aluminum body and heatsink, PMMA lenes
Driver	Tridonic Philips Lifud



CUTOUT & DIMENSION

MODEL	POWER	DIMENSION
AESTRL	10W	L90mm * W90mm * H90mm
	20W	L110mm * W110mm * H120mm
	30W	L130mm * W130mm * H135mm
	40W	L160mm * W160mm * H165mm



ORDERING INFORMATION

EXAMPLE : AESTRL-10W-80-30-45-PH-ND

Model	Wattage	CRI	CCT	Beam	DriverType	Dimming
AESTRL	10W	80	30	45	Ph	ND
AESTRL	10W	80	27 2700K	38°	Tr Tridonic	ND Non Dim
	20W	90	30 3000K	45°	Ph Philips	TD Triac Dim
	30W		35 3500K		Lf Lifud	VD 0/1-10VDim
	40W		40 4000K			DA DALI Dim
			50 5000K			
			57 5700K			
			65 6500K			