



## GARDEN LIGHT

### ALPHA FAMILY



### APPLICATION

Round pole-top mounted luminaire for outdoor installation on a pole diameter 60 mm, single or double supporting arm, with downward light distribution, and different beam types, high corrosion resistance die-cast copper-free aluminum body. Suitable for garden, pedestrian, parks, etc...

### APPROVALS & STANDARDS

Saudi Standard SASO 2902 *	Energy Efficiency, functionality & labeling requirements for lighting products -Part2-
IECEE certificate *	As per IEC60598-2-3:2002+A1:2011 IEC60598-1:2014+A1:2017
Power supply approval marks	UL/CSA/CE/ENEC/CCB/CCC
Degree of protection provided by enclosures, ingress protection(IP)	IEC 60529:2013

\*: Approvals and certificate are under process.

### TECHNICAL INFORMATION

FAMILY	ALPHA
Wattage	36W   72W
CRI	80
CCT	3000K   4000K   5000K   5700K   6000K   6500K
Beam	SYMMETRICAL   CYCLE ROUTE / PEDESTRIAN   STREET
Lumen	4320lm   8640lm
Finish	Silver   Gray   Black
Efficacy	120 lm/w
Material	Die-casting aluminum body and heatsink, PMMA lenes
Driver	Tridonic   Philips   Lifud
Ambient (Ta) Temperature	-30°C to +50°C

### BEAM TYPES


SYMMETRICAL



CYCLEROUTE/PEDESTRAIN



STREET



OSRAM

CREE


LUMILEDS

bridgelux



**DIMENSION**

MODEL	POWER	DIMENSION
AESAP	36W	Ø390mm * H578mm
	72W	



**ORDERING INFORMATION**

EXAMPLE : AESAP-36W-30-CR-S-Ph-ND

Model	Wattage	CCT	BeamType	BodyColor	DriverType	Dimming
AESAP	36W	30	CR	S	Ph	ND
AESAP	36W	27 2700K	SY SYMMETRICAL	S Silver	Tr Tridonic	ND Non Dim
	72W	30 3000K	CR CYCLEROUTE/PEDESTRAIN	B Black	Ph Philips	VD 0/1-10VDim
		40 4000K	SL STREET	G Gray	Lf Lifud	DA DALI Dim
		50 5000K				
		57 5700K				
		60 6000K				
		65 6500K				